Technical Data Sheet



Page 1

ULS Ultrasolve Cleaning Solvent

ULS is a fast-drying solvent specially formulated for the quick and efficient cleaning of electrical equipment. It offers excellent degreasing properties and a fast evaporation rate.

- Excellent degreasing properties; ideal for efficient cleaning of PCBs and electronic equipment
- Also removes flux residues and acrylic conformal coatings; versatile in use
- Fast evaporation rate; efficient cleaning processes
- CO, propelled aerosol version available; 20% more active cleaner

| Approvals | RoHS-2 Compliant (2011/65/EU): | | Yes | | |
|-------------------------|--|---|---|--|---|
| Typical Properties | Boiling Point (°C) Flash Point (°C) Density @ 20°C (g/ml) Inhalation Toxicity (ppm) Residue on Evaporation (ppm) Evaporation Rate | | >80 -20 0.79 300 1 16 (eth | er = 1) | |
| Description | | Packaging | | Order Code | Shelf Life |
| Ultrasolve Cleaning Sol | <u>vent</u> | 12ml Pen - Packed in 5 200ml Aerosol 400ml Aerosol 400ml Aerosol with Bru 1 Litre Bulk 5 Litre Bulk 25 Litre Bulk | | ULS12P ULS200D ULS400D ULS400DB ULS01L ULS05L ULS25L | 36 Months 36 Months 36 Months 48 Months 72 Months 72 Months 72 Months |

Directions for Use

ULS is suitable for cleaning PCBs, electronic equipment and components. It removes flux residues as well as offering efficient degreasing properties. In addition, it can be used to remove acrylic conformal coatings. Product contains flammable solvent so do not spray onto live electrical equipment or other sources of ignition. Immerse surface to be cleaned or spray onto surface to excess and allow to evaporate. A brush or foam tipped bud may be used to remove any stubborn deposits. For use on large scale production, ULS may be used in ultrasonic cleaning equipment which must be adapted for use with flammable liquids.

Revision 1: Oct 2013

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way, Ashby de la Zouch, Leicestershire LE65 1JR **T** +44 (0)1530 419 600 **F** +44 (0)1530 416 640 BS EN ISO 9001:2008 Certificate No. FM 32082