



New:
up to 8.000 mW/cm²

LED

LED Powerline AC

Max. irradiation intensity: up to 8.000 mW/cm²

Wavelength: 365, 385, 395 and 405 nm

Air cooled

System-Features

- High irradiation power
- Small dimensions
- Low weight
- Different wavelengths available

Advantages

- Low temperature load
- No heating phase

LED Powerline AC


The **LED Powerline AC** is a high-performance UV LED array for intermediate curing (pinning) and final curing for printing applications. Other applications are the curing of varnishes or UV-reactive adhesives and pottings.

The typical **LED service life is more than 20.000 hours***. The LEDs can be switched-on and -off as often as required, without any warm-up or cooling phase.

The **LED Powerline AC** is available in wavelengths of **365/385/395/405 nm +/- 10 nm**. This variety allows to adjust the wavelength to the application in question. Integrated air-cooling guarantees a reliable continuous operation over the whole ambient temperature area, without depending on huge external heat exchangers.

Special features

- The **LED Powerline AC** is electrically driven by a compact and efficient integrated module for top hat rail mounting or by the Hönle table unit LED **powerdrive**.
- Driving and monitoring of a LED segment up to a max. electric power of 400 W (depending on wavelength)
- Monitoring of LED segments regarding short-circuit, interruption and excess temperature
- Registration of operating hours of LED-segments
- Analogue dimming of the segments via a 0-10 V-signal
- Digital PLC-interface (Emergency-stop, LED-on, LED-failure, temperature warning)
- All modules BUS-controlled via RS485 and separate operation-display



Technical data

LED service life	> 20.000 hours *			
Irradiated area / output window:	75 x 20 mm other lengths on request			
dimensions in mm:	110 x 57 x 170 max. length application dependent			
wavelengths in nm	365	385	395	405
typical intensity in mW/cm ^{2**}	4000	6000	8000	8000
Cooling	air cooling			

* typical time for usage under standard environment conditions

** measured with Hönle LED sensor for UV meter

Advantages of LED technology

LEDs do not emit infrared irradiation. Thanks to the low temperature load on the substrate, even heat-sensitive materials can be irradiated. The different spectra guarantee safe and fast curing.

As LEDs do not need any warm-up phase, the LED heads can be switched on and off as often as required and they are immediately ready for operation at any time.



Dr. Hönle AG UV Technology, Lochhamer Schlag 1, 82166 Gräfelfing/München, Germany
Phone: +49 89 85608-0, Fax: +49 89 85608-148. www.hoenle.de

Operating parameters depend on production characteristics and may differ from the foregoing information. We reserve the right to modify technical data. © Copyright Dr. Hönle AG. Updated 09/13.